

GROUND FLOOR NOTES & ABBREVIATIONS

1). SEE DWG S1.1 FOR GENERAL NOTES AND LEGEND.

COORDINATE ALL WALL DIMENSIONS AND OPENINGS WITH ARCHITECTURAL DRAWINGS.

SEE ARCHITECTURAL DRAWINGS FOR GROUND FLOOR EXTERIOR CONCRETE SLAB LAYOUT, SLOPES, CONTROL JOINTS AND ELEVATIONS.

4). PROVIDE THICKENED SLAB EDGE (TE) AT ALL DOOR OPENINGS TO THE EXTERIOR. SEE DWG SS.3 FOR DETAIL.

5). TOP OF FOOTING ELEVATION = 98'-8" U.N.O.

DROP WALL FOOTINGS (DF) AS NECESSARY FOR UNDERGROUND PIPING. SEE DWG S5.3 FOR DETAIL.

7). PROVIDE #3 BAR x 3'-6" LG ABOVE SLAB REINFORCEMENT AT ALL RE-ENTRANT CORNERS IN SLAB ON GRADE (TYPICAL).

CJ = CONTROL JOINT. SEE DWG S5.3 FOR DETAIL

MCJ - MASONRY CONTROL JOINT. SEE DWG S5.2 FOR DETAIL

WF(XX) = CONTINUOUS WALL FOOTING. SEE SCHEDULE ON DWG 55.1.

F(XX) - SPREAD FOOTING. SEE SCHEDULE ON DWG S5.1.

= DROPPED FOOTING. SEE DWG \$5.3 FOR DETAIL MW(XX) = MASONRY WALL REINFORCING. SEE SCHEDULE ON DWG S5.1

= CONCRETE COLUMN. SEE SCHEDULE ON DWG S5.1.
= STEEL COLUMN. SEE SCHEDULE ON DWG S5.1.
= MASONRY COLUMN. SEE SCHEDULE ON DWG S5.1.

TE - THICKENED SLAB EDGE. SEE SCHEDULE ON DWG S5.1.

TS = THICKENED SLAB. SEE SCHEDULE ON DWG S5.1.

TOTAL = INDICATES DEPRESSED SLAB, SEE DWG S5.4 FOR DETAIL

ROOF FRAMING NOTES

1). SEE DWG S1.1 FOR GENERAL NOTES AND LEGEND.

TOP OF JOIST ELEVATION VARIES. REFER TO ARCHITECTURAL DRAWINGS FOR SLOPE AND HIGH/LOW POINTS, JOIST BEARING NOTED ON PLAN THUS

ROOF DECK SHALL BE 1 1/2", 20 GAGE, GALVANIZED TYPE B ROOF DECK.

4). SEE DWG S-5.4 FOR TYPICAL ROOF OPENING SECTION.

5). FOR LOCATION OF ADDITIONAL LOADS, COORDINATE w/ ARCHITECTURAL AND MECHANICAL DRAWINGS.

(XX) INDICATES SCHEDULED SIZE

BR-(XX) = CONCRETE ROOF BEAM. SEE SCHEDULE ON DWG S5.2 WP-(XX) = STEEL WALL CONNECTION PLATE. SEE SCHEDULE AND DETAIL ON DWG S5.2

LAKE COUNTY SCHOOLS
3 - FOUNDATION & ROOF PLANS UMATILLA HIGH SCHOOL
UMATILLA, FLORIDA
LAKE COUNTY SCHOOLS

BRPH

LUZNAR ROLL

5254.01\03-S2 06-06-03 03-S2.